

Ethylene Glycol (EG) Coolants North American Market	Color	Inhibitor Package										Meets Specifications							
		Light Duty		Heavy Duty				Notes				OEM						Other	
		Conventional High Silicate*	Conventional Low Silicate w/out SCA	Conventional Fully Formulated with SCA	Hybrid (HOAT)	OAT (2-ethyl-hexanoic acid)	OAT (other organic acid)	w/out Silicate	w/out Phosphate	w/out Borate	Full OAT	Daimler Chrysler	Ford	GM	CAT	Cummins	DDC	TMC RP329	ASTM D6210
<i>Passenger Car High Silicate</i>	Green	X										<2003	<2003	<1995					
Artic Blend™ Universal	Green		X									<2003	<2003	<1995					
Fleetguard Universal™ Low Silicate	Green		X									<2003	<2003	<1995					
Fleetguard Universal™ Recycled Coolant	Green		X									<2003	<2003	<1995					
Shell Shellzone® Low Silicate	Green		X									<2003	<2003	<1995					
Universal Low Silicate	Green		X									<2003	<2003	<1995					
Artic Blend™ HD Fully Formulated	Pink			X							X				X	X	X	X	X
CAT® Diesel Engine Antifreeze Coolant	Pink			X							X				X	X	X	X	X
Detroit Diesel PowerCool®	Pink			X							X				X	X	X	X	X
Fleetguard ES Compleat™	Blue			X											X	X	X	X	X
Fleetguard Fleetcool™	Pink			X							X				X	X	X	X	X
Fleetguard Fleetcool™ Recycled Coolant	Green			X							X				X	X	X	X	X
Old World Industries Fleet Charge®	Pink			X							X				X	X	X	X	X
Prestone® Heavy Duty	Pink			X							X				X	X	X	X	X
Artic Blend™ G-Plus	Yellow				X						X	X					X	X	
DaimlerChrysler / Mopar® 2003	Orange				X						X	X						X	X
Fleetguard Fleetcool™ EX	Pink				X						X			X				X	X
Ford Motorcraft® Premium Gold	Yellow				X						X	X						X	X
Peak CF-EXL® Extended Life Coolant	Yellow				X						X	X						X	X
Valvoline Zerex® G-05	Yellow				X						X	X						X	X
CAT® ELC	Red					X				X	X				X	X**	X	X	X
ChevronTexaco Delo™ Extended Life Coolant	Red					X				X	X				X	X**	X	X	X
GM DEX-COOL®	Orange					X				X	X			X					
Prestone® Extended Life 5/150	Orange					X				X	X			X					
Shell Rotella® Extended Life Coolant	Red					X				X	X			X	X**	X		X	X
Texaco Havoline® DEX-COOL®	Orange					X				X	X			X					
Texaco Havoline® Extended Life Coolant	Red					X				X	X			X	X**	X**		X	X
Valvoline Zerex® ExtremeLife™ 5/150	Orange					X				X	X			X					
Valvoline Zerex® Extended Life Extreme 3/300	Red					X				X	X			X	X	X		X	X
Detroit Diesel PowerCool Plus®	Red								X	X	X			X	X	X			X
Old World Industries Final Charge®	Red								X	X	X			X	X	X			X
Fleetguard ES Optimax™	Red								X	X	X			X	X	X			X
Compatibility***																			
Conventional High Silicate		X																	
Conventional Low Silicate w/out SCA			X																
Conventional Fully Formulated with SCA				X			X												
Hybrid (HOAT)				X			X												
OAT (2-ethyl-hexanoic acid)							X												
OAT (other organic acid)							X												

Comments

*Do not use SCA with conventional high silicate antifreezes

**Requires special silicate additive liquid or silicate filter to protect certain gasket materials

***Mixing different types of antifreezes can reduce their corrosion protection. Engine manufacturers recommend a 10% limit on mixing coolant types.